

3-Way Catalysts

Product Specifications



Features

performance.


Our 3-way/NSCR Catalysts are manufactured using the most advanced emission reduction technology. They are designed to reduce harmful pollutants such as Hydrocarbons (HC), Carbon Monoxide (CO), NOx and Volatile Organic Compounds (VOC's)

and

CPhoenix Catalyst

worry-free

Phoenix Catalyst cores are housed with 100% catalyst coating. All of our core parts are made in the USA



Reductions & Benefits

- ✓ Nitrogen Oxides Reduction by 60-99%
- ✓ Carbon Monoxide (CO) by 80-99%
- ✓ Hydrocarbons (HC) by 50-90%
- ✓ Volatile Organic Compounds by 90% (VOC's)

Housing: High performance Stainless Steel

Typical Catalyst Life: Approximately 3,000 hours

Phoenix Catalyst is committed to providing high

emission reductions. Our catalysts can be found

on any equipment or machine such as skid steers,

mini excavators, concrete cutting & polishing

effective

Operating Temperatures: Exhaust must be 200°C

(400°F), not to exceed 750°C (1380°F)

cost

machinery, forklifts and generator sets.

Maintenance: Maintenance free, with proper usage.


Compressed air can be used to remove any

particulate build up.

Backpressure: 1-4" inches of water is typical

Warranty: Up to one year of original invoice date or up to 1,000 operational hours or whichever happens

first.



Key Benefits

- > Next Day delivery available
- ➤ MEET & EXCEED Government Emissions Standards
- ➤ Phoenix has the most complete line up of in stock Diesel Oxidation (2-Way) & 3-Way Catalysts
- ➤ Easy, FAST installation and minimal maintenance
- > Competitive Pricing
- ➤ Phoenix Catalysts are manufactured using **NGT Technology** (Next Generation Technology)
- ➤ Phoenix Catalysts can be used with any other Emissions Reducing Technology

© 2022 Phoenix Catalyst Company Ltd info@phoenixcatalystltd.com ■ 1-877-997-8462